

Technical Data Sheet

FMR268(finish) FORME® CRYSTAL

Product Code	FMR268(finish)
Product Name	Forme® Crystal Lever
Product Description	Crystal Lever on Round Minimal Fixa Rose
Product Base Material	Zinc Alloy – high grade
Available Finishes	Polished Chrome (PC) Yester Bronze (YB) Satin Chrome (SC)
Other Information	To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will damage the applied finish. Supplied 2 x Bolt through Fixing, 2 x Fixa plates, Wood Screws, 8 mm x 8 mm x 100 mm Split Spindle, 1 x Loctite coated Grub Screws & Allen Key. Bolt through Fixing and Grub Screws must be used. 10 Year Mechanical Guarantee subject to fitting requirements.
Matching WC Turn:	FMRWC(finish)
Matching ESC:	Key: FMRK(finish) Euro: FMRE(finish)

Dimensions

FMR268 Lever Dimensions:


A: 50mm

B: 138mm

C: 10mm

D: 60mm

Total Lever & Rose Length: 156mm



Product Image



Finish Photographed: Yester Bronze (YB)

Care of Finish

In the unusual event of this product failing mechanically, we will replace it free of charge, providing you can supply us with the faulty product and a receipt to show proof of purchase. If the items are not fitted in accordance with the fitting instructions, in a correct application, this may not apply.

Products have an applied finish, and we do recommend regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If this is not effective in removing accumulated deposits, try using a PH-neutral soap on a soft cloth, then remove the soap immediately after application, with the help of a clean, moist, soft cloth. Under no circumstances should you use an abrasive/hard tool, chemical, acidic or abrasive substance to clean these products. This will break down the applied finish. The finish may chip or scratch if subjected to impact from sharp items such as keys and jewellery.

Please be aware that in environments where there are high concentrations of chemicals in the air, for example from the use of low-quality paint or corrosive agents, corrosion and damage may occur to the surface of the product. Products should therefore not be fitted in such environments, until the high concentration of chemicals in the air has subsided.

the finish matters